




PROFILE MIKE 7661



**PROFILE MIKE**

painting aluminum, plastic

7662 7661


1xGU10, max 15W only LED



PROFILE ZOOM LED 7625



PROFILE INDIA 7657




**PROFILE INDIA**

painting aluminum, plastic

7656 7657

1xGU10, max 15W only LED



**PROFILE ZOOM LED**

painting aluminum, plastic

7623 3000K 7625 3000K

7624 4000K 7626 4000K

BEAM CONE


BEAM ANGLE 15°



BEAM ANGLE 50°



PROFILE FOKUS 7621



**PROFILE FOCUS LED**

painting aluminum, plastic

7618 3000K 7621 3000K

7620 4000K 7622 4000K

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection
7618	10W LED	3000K	600 lm	36°	>90	~220-230 V, 50/60 Hz	□	>0.9	IP20
7620	10W LED	4000K	600 lm	36°	>90	~220-230 V, 50/60 Hz	□	>0.9	IP20
7621	10W LED	3000K	600 lm	36°	>90	~220-230 V, 50/60 Hz	□	>0.9	IP20
7622	10W LED	4000K	600 lm	36°	>90	~220-230 V, 50/60 Hz	□	>0.9	IP20
7623	9W LED	3000K	600 lm	15-50°	>90	~220-230 V, 50/60 Hz	□	>0.9	IP20
7624	9W LED	4000K	660 lm	15-50°	>90	~220-230 V, 50/60 Hz	□	>0.9	IP20
7625	9W LED	3000K	600 lm	15-50°	>90	~220-230 V, 50/60 Hz	□	>0.9	IP20
7626	9W LED	4000K	660 lm	15-50°	>90	~220-230 V, 50/60 Hz	□	>0.9	IP20