


### PROFILE STORE LED 5W

stal lakierowana / painted steel / лакирована сталь

5947 ○ WH 6824 ● BL

PROFILE STORE LED 5W 6824 BL




### PROFILE STORE LED 7W

stal lakierowana / painted steel / лакирована сталь

5948 ○ WH 6825 ● BL

PROFILE STORE LED 7W 6825 BL


PROFILE SHOW LED 12W 9423 WH



### PROFILE SHOW LED 12W

aluminium / aluminium / алюминия

9423 ○ WH 9424 ● BL



### PROFILE STORE LED 12W

stal lakierowana / painted steel / лакирована сталь

5950 ○ WH 6826 ● BL

PROFILE STORE LED 12W 5950 WH

Item No.	POWER	COLOUR TEMP.	LUMINOUS FLUX	BEAM ANGLE	COLOUR RENDERING INDEX (CRI >)	INPUT	SAFETY TYPE	POWER FACTOR	INGRESS PROTECTION	LIFETIME
9423, 9424	1x12W COB LED	4000K	1500 -1650 lm	24°	80	~200-240V, 50Hz	□	0.5	IP 20	8 000 h

Item No.	POWER	COLOUR TEMP.	LUMINOUS FLUX	BEAM ANGLE	COLOUR RENDERING INDEX (CRI >)	INPUT	SAFETY TYPE	POWER FACTOR	INGRESS PROTECTION	LIFETIME
5947, 6824	5x1W LED	4000K	450 - 500 lm	30°	80	~200-240V, 50Hz	□	> 0.5	IP 20	8 000 h
5948, 6825	7x1W LED	4000K	630 - 700 lm	30°	80	~200-240V, 50Hz	□	> 0.5	IP 20	8 000 h
5950, 6826	12x1W LED	4000K	1080 -1200 lm	30°	80	~200-240V, 50Hz	□	> 0.5	IP 20	8 000 h